





标 记
MARKPCN编号/变更内容
ECN NO/DEFINITION修 改
REVISE日 期
DATE核 准
APPROVE

PIN

尺寸 (mm)



	A	B	C
02	2.50	7.40	6.50
03	5.00	9.90	9.00
04	7.50	12.40	11.50
05	10.00	14.90	14.00
06	12.50	17.40	16.50
07	15.00	19.90	19.00
08	17.50	22.40	21.50
09	20.00	24.90	24.00
10	22.50	27.40	26.50
11	25.00	29.90	29.00
12	27.50	32.40	31.50



SPECIFICATIONS

- 1.Current Rating: 3A AC, DC
- 2.Voltage Rating: 250V AC, DC
- 3.Temperatuer Range: -25°C~+85°C
- 4.Contact Resistance: 20mΩ Max
- 5.Insulation Resistance: 1000MΩ Min
- 6.Withstanding Voltang: 1000V AC/minute
- 7.Material: Wafer PA66
PIN Brass Tin-plated

Circuit 1



1	基座	PA66	本色	
序号	品名	材质	电镀/颜色	备注



深圳市虹成电子有限公司

品名

TITLE

料号

PART NO

一般公差

TOLERANCE

X.±0.25

X.'±2'

.X±0.25

.X'±1'

.XX±0.15

.XX'±0.5'

.XXX±0.10

.XXX'±0.5'

比列

SCALE

1:1

单位

UNIT

张数

PART NO

版本

REV

A

制图

DRAW

审核

CHECKED

批准

APPROVE

AhYe

夏操云

赵亮亮

胶壳

HC-JK-5264-5Y